



Product Data Sheet

Muxx 15W 40 CH-4 High performance heavy duty multigrade engine oil. Specially engineered for exceptional performance in the latest model turbo charged diesel engines. The Ultra modern technology of this product offers a long life with extended drain capability to maximize the engine durability

Suitable for modern passenger cars, tractors , Off Highway equipment and all types turbo charged, super charged and naturally aspirated diesel engines operating under severe conditions

APPLICATIONS

Muxx 15W 40 is recommended for naturally aspirated, highly supercharged and turbocharged diesel engines operating under severe duty conditions in all seasons .

BENEFITS

Muxx oil provide excellent resistance against wear and deposits in automotive supercharged diesel engines • Have exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature. • Provide absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves. • Maintain a high order of engine cleanliness

CHARACTERISTICS

SAE GRADE	15W- 40
Kin. Vis. cSt @ 100°C , ,.	13 – 15
Viscosity Index	Min. 120
Flash point (COC), °C Min.	230 – 250
Pour Point °C Max	(-) 6
TBN mg KOH/gm	10 – 13

HEALTH & SAFETY : These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

India office (licensee) : Plot No.S3 & S4, TSIC, Autonagar, Hyderabad – 500070.

Germany Office : Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany

Taiwan office : Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New Taipei City, Taiwan.

For further information please email us on info@muxx.in