



## **Product Data Sheet**

**Muxx 15W 40 CI-4+** Superior performance semi synthetic heavy duty multigrade engine oil containing high additive dosage and blended with best quality base stocks. It gives double drain period advantage over the conventional multigrade diesel engine oils.

Suitable for modern passenger cars, tractors , Off Highway equipment and all types turbo charged, super charged and naturally aspirated diesel engines operating under severe conditions

### **APPLICATIONS**

Muxx 15W 40 is recommended for naturally aspirated, highly supercharged and turbocharged diesel engines operating under severe duty conditions in all seasons .

### **BENEFITS**

Muxx oil provide excellent resistance against wear and deposits in automotive supercharged diesel engines • Have exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature. • Provide absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves. • Maintain a high order of engine cleanliness

### **CHARACTERISTICS**

SAE GRADE	15W- 40
Kin. Vis. cSt @ 100°C , ,.	13 – 15
Viscosity Index	Min. 120
Flash point (COC), °C Min.	230 – 250
Pour Point °C Max	(-) 6
TBN mg KOH/gm	10 – 13

**HEALTH & SAFETY** : These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

**India office (licensee)** : Plot No.S3 & S4, TSIIIC, Autonagar, Hyderabad – 500070.

**Germany Office** : Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany

**Taiwan office** : Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New Taipei City, Taiwan.

For further information please email us on [info@muxx.in](mailto:info@muxx.in)