



MUXXOL REFRIZZ Oil

PRODUCT DESCRIPTION:

Muxxol Refrizz oil is blended using highly refined, specially treated straight mineral paraffinic oils designed for low temperature applications. It has low pour points and excellent fluidity at low temperatures by virtue of being wax-free. Special additives minimise the system deposits and offer long service life. This oil has good chemical stability and rapid solubility in liquefied refrigerants. It ensures high condenser efficiency and reduced compressor valve maintenance due to less amount of deposit formation.

FEATURES AND ADVANTAGES:

- High Quality Base Oil – superior quality Paraffinic base oils offer very good low temperature properties and excellent heat transfer even at low temperatures.
- ✓ Low Wax Content – low wax forming tendency ensures efficient evaporator operation and low temperature fluidity.
- ✓ Excellent Chemical Stability – possesses excellent high temperature and oxidation stability even at high compressor discharge temperatures.
- ✓ Superior control of sludge and deposit control ensure longer service life.
- ✓ Good Lubrication Property – prevents system wear. Offers protection and maintains

PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual	clear liquid
Density, g/cc @ 15°C	ASTM D 1298	0.875
Kin. Viscosity @ 40°C, cSt	ASTM D 445	68.5
Flash Point (PMCC), °C, min	ASTM D 92	230
Pour Point °C,	ASTM D 97	-27
Copper Corrosion @ 100° C, 3hrs	ASTM D 130	1a
Total Acid Number mg KOH/g	ASTM D 974	0.05

HANDLING AND STORAGE:

Handling: Use oil resistant gloves & wear safety goggles.

Storage: Store in a cool, dry, well-ventilated place and away from direct sunlight. Store away from all incompatible materials. Keep containers closed when not in use.

Shelf Life: One year from the date of manufacture, if product stored in original container,

PACKING: MUXXOL GUN DRILLING Oil is available in 20 ltr 50 ltr and 210 ltr barrels.

- India office (licensee): Plot No.S3 & S4, TSIIC, Autonagar, Hyderabad – 500070.
 - Germany Office: Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany.
 - Taiwan office: Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New City, Taipei,
- For further information please email us on info@muxx.in