



MUXXOL VACCUM OILS

PRODUCT DESCRIPTION:

MUXXOL VACUUM OILS are developed based on highly refined base oils and fortified with multifunctional additive, especially having good demulsifying properties. **Muxxol Vacuum oils** possess very low vapour pressure and provide better lubrication properties.

FEATURES AND ADVANTAGES:

- Excellent ageing characteristics.
- Better demulsification properties.
- Provide Stable lubricating film with low coefficient of friction.
- Low volatility.

TYPICAL SPECIFICATION:

PROPERTIES	TEST METHOD	TYPICAL VALUES	
ISO VG	-	T 68	T 100
Density @ 29.5°C, g/ml	ASTM D 1298	0.86	0.867
Kinematic Viscosity @ 40°C, cSt	ASTM D 445	61.2 – 74.8	80 - 100
Viscosity Index, min	ASTM D 2270	100	100
Flash Point (COC), °C, min	ASTM D 92	190	210
Pour Point, °C, max	ASTM D 97	-18	-12
Copper Corrosion@ 100deg C, 3 hrs	ASTM D130	1a	1a
TAN, mg of KOH/g, max	ASTM D 974	1.0	1.0

HANDLING AND STORAGE:

Handling: Use oil resistant gloves & wear safety goggles.

Storage: Store in a cool, dry, well-ventilated place and away from direct sunlight. Store away from all incompatible materials. Keep containers closed when not in use.

Shelf Life: One year from the date of manufacture, if the product is stored in the original container, unopened and dry, in a well-ventilated location.

PACKING: MUXXOL VACUUM series are available in 20 ltr 50 ltr and 210 ltr MS /HDPE barrels

- India office (licensee): Plot No.S3 & S4, TSIC, Autonagar, Hyderabad – 500070.
- Germany Office: Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany.
- Taiwan office: Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New City, Taipei,
For further information please email us on info@muxx.in