



MUXXOL Chuck EEZ Paste

PRODUCT DESCRIPTION:

MUXXOL Chuck EEZ Paste is fully synthetic high performance chuck paste for lubricating friction and sliding points under high and impact loaded loads, Which helps to prevent fretting corrosion on the chucks.

APPLICATIONS:

Muxxol Chuck EEZ Jaw Paste is recommended as assembly lubrication paste for cnc and other machine tools and chuck jaws. Suitable to lubricating of areas in filing, labeling, packinging machine where high level vibrating stresses are encountered. It can be used on Power chucks standard chucks, fasteners,press fits and Wear Guides and ways.

FEATURES AND ADVANTAGES:

- ✓ Good Resistence to water, cooling lubricants and other chemicals.
- ✓ High pressure and heavy load carrying capabilies.
- ✓ Good Corrosion protection.
- ✓ Prevents Stick-slip.
- ✓ Highly economical due to wide area coverage.satile use.

Tests	Test Method	Typical value
NLGI GRADE	-	2
Appearance / Color	Visual	Smooth & Tacky / Dull White
Base Oil	-	POA
Thickener	-	Lithium Complex
Four -Ball Weld Load,N/cm²	IP-239	2000
Solid Lubricants	-	PTFE
Drop Point, deg C	ASTM D-2265	280
Water Washout	ASTM D-1264	2 % Max
Operating temperature range , deg c		-20 to 200

HANDLING AND STORAGE:

Handling: Use oil resistant gloves & wear safety goggles.

Storage: Store in a cool, dry, well-ventilated place and away from direct sunlight. Store away from all incompatible materials. Keep containers closed when not in use.

Shelf Life: One year from the date of manufacture, if the product is stored in the original container, unopened and dry, in a well-ventilated location.

- India office (licensee): Plot No.S3 & S4, TSIIC, Autonagar, Hyderabad 500070.
- Germany Office: Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany.
- > Taiwan office: Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New Taipei City, Taiwan.
- For further information please email us on info@muxx.in