



Product Data Sheet

Muxx MP-3 Grease (Red)

DESCRIPTION

- Modified lithium soap based high temperature, water resistant grease.
- Premium quality multipurpose grease of NLGI 3 consistency.
- Meets IS 12203 : 99 (Reaffirmed 2009) specification.

APPLICATIONS

- Recommended for all types of anti-friction bearings used in automobiles including heavy duty commercial vehicles.

BENEFITS

- Excellent thermal and structural stability.
- Provides high oxidation resistance.
- Offers complete protection to anti-friction bearing.

CHARACTERISTICS

Appearance	Red
Texture	Medium Fibrous
Soap Type	Lithium
Worked Penetration 60st @ 25°C	Min 220 – Max 250
Drop Point	Min 190
Free Alkalinity (as LiOH) % by mass	Max 0.1
Copper Strip Corrosion	-ve
Bearing Performance Test	passes

India office (licensee) : Plot No.S3 & S4, TSIC, Autonagar, Hyderabad – 500070.

Germany Office : Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany

Taiwan office : Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New Taipei City, Taiwan.

For further information please email us on info@muxx.in