



MUXXOL FLEX 710

PRODUCT DESCRIPTION:

MUXXOL FLEX 710. It is an aromatic oil. This product is an excellent ingredient for the manufacture of various rubber/ rubber allied products. This product is having high unsaturated hydrocarbons which exhibits higher solvency. This product is fully compatible with Natural rubber and most unsaturated rubber polymers.

FEATURES AND ADVANTAGES:

- MUXXOL FLEX 710 is aromatic type of rubber process oil with good solvency.
- MUXXOL FLEX 710 is higher viscosity and is specifically designed for use as an extender oil in the manufacture of Rubber & Polymers.
- Suitable for use in manufacture of automobile rubber tyres, belting, battery case etc. Where colour is not an important parameter. It was specially developed for use with natural and SBS rubber.

SPECIFICATION:

PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual	Greenish Viscous liquid
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	20 – 28.5
Flash Point (COC), °C, Min	ASTM D 92	218
Pour Point, °C, Max	ASTM D 97	+18
Aniline Point, °C	ASTM D 611	39.5 – 52
Aromatics, Wt %	ASTM D 2007	70
Saturates, Wt %	ASTM D 2007	18
Polar Compounds, Wt %	ASTM D 2007	12

HANDLING AND STORAGE:

Handling: Use oil resistant gloves & wear safety goggles.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from all incompatible materials. Keep containers closed when not in use.

Shelf Life : Three years from the date of manufacture in unopened containers, stored under ambient conditions.

PACKING: MUXXOL FLEX 710 is available in 210 Ltr MS Barrel. This product can be supplied in tanker loads as well.

- **India office (licensee) :** Plot No.S3 & S4, TSIC, Autonagar, Hyderabad – 500070.
- **Germany Office :** Muxx Oil GmbH, Frankenhauser Str. 15, 12249 Berlin, Germany.
- **Taiwan office :** Muxx Oil GmbH 3F, No.215, Zhongzheng Rd. Shulin Dist. New Taipei City, Taiwan.
- For further information please email us on info@muxx.in